| Product data sheet for household cooker hoods according to regulation (EU) No. 65/2014 | | |
|--|-----------------|------|
| Brand | PYRAMIS ECOLINE | |
| Model | 065038901 | |
| Annual Energy Consumption (AEC _{hood}) | kWh/a | 63 |
| Energy Efficiency Class | | D |
| Fluid Dynamic Efficiency (FDE _{hood}) | | 8,3 |
| Fluid Dynamic Efficiency Class | | E |
| Lighting Efficiency (LE _{hood}) | lux/W | 46 |
| Lighting Efficiency Class | | А |
| Grease Filtering Efficiency (GFE) | % | 70 |
| Grease Filtering Efficiency Class | | D |
| Air Flow at minumum speed in normal use | m³/h | 210 |
| Air Flow at maximum speed in normal use | m³/h | 455 |
| Air Flow in use intensive or boost setting | m³/h | - |
| Acustic Power emission in normal use at minimum speed | dB | 44 |
| Acustic Power emission in normal use at maximum speed | dB | 64 |
| Acustic Power emission in boost mode | dB | - |
| Power Consumption in off mode (Po) | w | 0 |
| Power Consumption in standby mode (Ps) | w | - |
| Integration Directive E | U 66/2014 | |
| Time Increase Factor (f) | | 1,7 |
| Energy Efficiency (EEI _{hood}) | | 88,8 |
| Airflow at best efficiency point (Q _{BEP}) | m³/h | 237 |
| Pressure at best efficiency point (P _{BEP}) | Pa | 125 |
| Electric power input at the best efficiency point (W _{BEP}) | w | 99 |
| Electric power input for lighting system (W _L) | w | 2 |
| Avarage illuminance on the cooking surface (E _{middle}) | lux | 92 |